



## Sonost 3000

ultrasound bone densitometry with 6,4" touch screen

- easy to operate by intuitive software and integrated PC
- comfortable operation due to automatic moveable probes
- comprehensive report by issuing T- and Z - Score
- output of measuring results by integrated or external printer (optional)
- no radiation exposure
- most helpful for gynaecologists, general practitioners and internists

# Specifications

Performance	
Measurement	Calcaneus
Testing Time	ca. 15 seconds
Measurement Results	bone mineral density, bone quality index (BQI) deduced from BUA and SOS
Accuracy	SOS (C.V.%) 0,2; BUA (C.V.%) 1,5; BQI (C.V.%) 1,5
Operation	automatic moving ultrasound probes with gel pads (without water)
Probe Distance	25 mm - 100 mm
Printer	integrated thermo printer external printer (optional)
System Requirements	
Connectors	2x USB, VGA, PS2, power connection
Data Input	by integrated touch screen display or external mouse and keyboard
Display	6,4" TFT colour touch screen
Hard disc	storage of ca. 10.000 patient data
Environmental Conditions	
Operating Temperature	10 - 40 °C
Humidity	30 - 75% relative humidity
Operating Voltage	AC220V - 240V, 50 / 60Hz
Dimensions & Weight	
Dimensions	32 cm x 62 cm x 30 cm
Weight	12 kg

## Software



## Dimensions 32x62x30 cm, about 12 kg



medical **ECONET**

Mainstr. 6 c - d, 45768 Marl - Germany

t: +49 (0) 2365 924 37-0 info@medical-econet.com  
f: +49 (0) 2365 924 37-55 www.medical-econet.com

CE 0123

Dealer

\*Changes and errors without notice.